

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-86-92  
Relating to Certification of New Motor Vehicles

MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Mitsubishi Motors Corporation exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

<u>Engine Family</u>	<u>Displacement Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
JMT2.4T5FBCX	2.4 (143.4)	Exhaust Gas Recirculation Three-Way Catalyst Oxygen Sensor (Combustion Chamber Valve) (Electronic Port Fuel Injection)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

<u>Loaded Vehicle Weight</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per mile</u>
0-3750	0.39	9.0	1.0

The following are the certification emission values for this engine family:

<u>Loaded Vehicle Weight</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0-3750	0.26	2.4	0.1

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.) and with Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 23<sup>rd</sup> day of July, 1987.

  
K. D. Draehand, Chief  
Mobile Source Division

1987 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Mitsubishi Motors Corp. Executive Order No. A-86-92

ABBREVIATIONS

<u>Ignition System</u>	<u>Exhaust Emissions Control System</u>	<u>Special Features</u>
CA -Centrifugal Advance	AIP -Air Injection-Pump	CCV-Combustion Chamber Valve
ECU -Electronic Control Unit	AIV -Air Injection-Valve	CFI-Central Fuel Injection or Throttle body Injection
EI -Electronic Ignition	DBC -Dual Bed Catalyst	DID-Diesel Injection-Direct
ESAC-Electronic Spark Advance Control	EGR -Exhaust Gas Recirculation	DIP-Diesel Injection-Prechamber
VA -Vacuum Advance	EIC -Electronic Injection Control	EFI-Electronic Fuel Injection
VR -Vacuum Retard	EM -Engine Modification	IC -Intercooler or Aftercooler
	OC -Oxidation Catalyst	MFI-Mechanical Fuel Injection
	OS -Oxygen Sensor	OBD-On-Board Diagnostics
	HOS -Heated Oxygen Sensor	TC -Turbocharger
	SPL -Smoke Puff Limiter or Throttle Delay	
	TOC -Trap Oxidizer, Continual	
	TOP -Trap Oxidizer, Periodical	
	TWC -Three Way Catalyst	
	WUOC -Warm-Up Oxidation Catalyst	
	WUTWC-Warm-Up Three-Way Catalyst	

Fuel System

CFI, CL, DID, DIP, EFI, MFI  
nV-nVenturi Carburetor

Issued :  
Revised:

## 1988 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Mitsubishi Motors Corp.  
 Engine Family JMT2.4T5FBCX Evaporative Family I  
 Passenger Cars      Light-Duty Trucks X Medium-Duty Vehicles      Gas X Diesel       
 Engine CID (liter) - Type 143.4 (2.4) - L4  
 ECS (Special Features) EGR+OS+TWC (CCV+EPFI)

Engine Code	Vehicle Models (If Coded see attachment)	Trans.	ETW	Ign. System ESAC Part No.	Fuel System CL,EFI Part No.	EGR Valve Part No.	Catalyst Part No.
BA	Mitsubishi Wagon	L4	3625	Distributor	Fuel Injector	K5T58776	MD096609
ABA			3750	T3T64171	M275		
					Throttle Body		
	Mitsubishi Van		3250		AC50-102		

Note: Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment.

Issued :  
 Revised: